




24W Surface ceiling spot, IP20.

Complete with 600mA driver.

Complies with standard EN60598-1 and any other specific standards.






Dimensions




Physical Specification

Item Group	13 Wall & Ceiling LED
Family	The Dark Light Mirror Cylinders
Order Code	12124X
Colour	White/Black
Material	Aluminium
Shape	Circular
Height	58mm
Diameter	160mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No


Gear		Built In	
Fitting + Driver			
Input Voltage		220-240V	
50 Hz		Yes	
60 Hz		Yes	
Safety Class			
Power(Watts)		24W	
IP Rating		IP20	
Light Source		LED built in	
Dimmable		No	

Fitting			
Input Type		Constant Current	
Input Current		600mA	
Voltage		36V	
Safety Class			
Power(Watts)		21,6W	
IP Rating		IP20	
Light Source		LED built in	
LED Type		SMD 3030	
LED Brand		Sanan	
LED Number		18	
F Mark			

Gear			
Gear Type		Led Driver	
Input Voltage		220-240V	
50 Hz		Yes	
60 Hz		Yes	

Power(Watts)	16,8-25,2W
Power Factor	0,9
Constant Current	Yes
600mA	28-42
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	-20°C...+60°C
Operating Temp	85°C
Brand	Eaglerise
Protection	Over Load Protection, Over Voltage Protection, Short circuit Protection

Illumination Data

Colour Temperature	3000K
Lumen Output	1900lm
Light Efficiency	80lm/W
CRI	90
Beam Angle	38°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Weight	0.960kg
Pcs/Carton	20
Barcode	5291889074502
HS Code	9405413990

Certification & Warranty

